(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 14 July 2005 (14.07.2005)

PCT

(10) International Publication Number WO 2005/064299 A2

(51) International Patent Classification⁷:

G01L

(21) International Application Number:

PCT/JP2004/019828

(22) International Filing Date:

27 December 2004 (27.12.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003-435068 26 December 2003 (26.12.2003) JP 2004-106923 31 March 2004 (31.03.2004) JP

(71) Applicant (for all designated States except US): TOY-OTA JIDOSHA KABUSHIKI KAISHA [JP/JP]; 1, Toy-ota-cho, Toyota-shi, Aichi, 4718571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SANO, Akihito [JP/JP]; 2300-2, Kitagata, Kitagata-cho, Motosu-gun, Gifu, 5010431 (JP). MOCHIYAMA, Hiromi [JP/JP]; 206, Guranpasu Ikemi, 2-177, Ikemi, Tenpaku-ku, Nagoya-shi, Aichi, 4680067 (JP). TAKESUE, Naoyuki [JP/JP]; 203, Shiruku Ichibankan, 2-403, Kounosu, Tenpaku-ku, Nagoya-shi, Aichi, 4680003 (JP). KIKUUWE, Ryo [JP/JP]; 3B, Mailusutone Izumi, 2-20-9, Izumi, Higashi-ku, Nagoya-shi, Aichi, 4610001 (JP). FUJIMOTO,

Hideo [JP/JP]; 201, Jarudan Shinkanayama, 1-8-19, Kanayama, Naka-ku, Nagoya-shi, Aichi, 4600022 (JP).


- (74) Agent: OHKAWA, Hiroshi; 2-5, Meieki 3-chome, Nakamura-ku, Nagoya-shi, Aichi, 4500002 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CONVEXO CONCAVE AMPLIFYING DEVICE AND CONVEXO CONCAVE DETECTING METHOD BY USE THEREOF, DEFORMATION SENSING DEVICE AND CONVEXO CONCAVE DETECTING METHOD BY USE THEREOF, AND CONVEXO CONCAVE POSITION EXHIBITING DEVICE AND CONVEXO CONCAVE POSITION EXHIBITING METHOD



(57) Abstract: A convexo concave amplifying device for exhibiting a convexo concave by amplifying a sense of a convexo concave of an object, comprising a sensing member and an exhibiting member. The sensing member 101 comprises a flexible sheet able to contact with the surface of the object O and to deform along the surface of the object. The exhibiting member 120 that is formed on a surface of the flexible sheet and has a deformation resistance smaller than that of the flexible sheet in at least one of directions orthogonal to a direction of thickness of the flexible sheet. With such construction, the object convexo concave can be amplified and exhibited. A deformation sensing device for sensing a deformation thereof

comprising a capsule deformable by stress, a viscous fluid F contained in the capsule, and a relative movement sensing member that is disposed inside of the capsule and senses a relative movement against the viscous fluid. With such construction, property of the object such as the convexo concave or the stress can be detected.

0 2005/064299 A2 IIII